

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
8 January 2004 (08.01.2004)

PCT

(10) International Publication Number
WO 2004/004107 A1

(51) International Patent Classification⁷: **H02M 5/257**

(21) International Application Number:
PCT/GB2003/002785

(22) International Filing Date: 27 June 2003 (27.06.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0214841.9 27 June 2002 (27.06.2002) GB

(71) Applicant and

(72) Inventor: **SHLAIMOUN, Zia** [GB/GB]; 21 Glebelands
Avenue, South Woodford, London E18 2AB (GB).

(74) Agent: **ACKROYD, Robert**; W.P. Thompson & Co.,
Eastcheap House, Central Approach, Letchworth Garden
City, Hertfordshire SG6 3DS (GB).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND DEVICE FOR CONTROLLING VOLTAGE



(57) **Abstract:** A voltage control device for connection to an electrical supply having an alternating supply voltage, and relative method for controlling voltage. The device comprising: an input (P1, P2, P3) having an input voltage, said input for connection to the electrical supply; an output (L1, L2, L3) having an output voltage; means for comparing the output voltage with a predetermined voltage (V1, V2, V3) and generating a comparison signal; means to adjust (THY1, THY2, THY3) the output voltage in response to the comparison signal, said means being connected to the input and output; whereby the output voltage is maintained substantially at the predetermined voltage. Preferably, the means to adjust the output voltage comprise means to delay the onset of the rise of output voltage within one half-cycle. More preferably, the means to delay comprises a thyristor module.

WO 2004/004107 A1